

ESP8266_AT_V1.6.2_18_06_08 Release Notes

1. Fix station connecting behavior after upgrading from an old version.
2. Fix wrong SSID query when the length of SSID is 32 bytes.
3. Optimize AT+CIUPDATE behavior.

Github:

[ESP8266 NonOS SDK and AT Bin on Github](#)

ESP8266_AT_V1.6.1_18_02_13 Release Notes

1. Fix an issue that light sleep current is larger than before.

ESP8266_AT_V1.6.0_18_02_06 Release Notes

1. Update AT version to 1.6.0.0;
2. Add a new command `AT+SYSMSG` to enable some report information;
3. Add a new command `AT+CWCOUNTRY` ;
 - `AT+CWCOUNTRY=<country_policy>,"country_code",<start_channel>,<total_channel_number>`
4. Add new command `AT+CIPSERVERMAXCONN` ;
 - `AT+CIPSERVERMAXCONN=<num>`
5. Update command `AT+CWLAP` ;
 - `AT+CWLAP =<ssid>[,<mac>,<ch>,<scan_type>,<scan_time_min>,<scan_time_max>]`
6. Update command `AT+CWLAPOPT` ;
 - Mask changes from 0x7F to 0x7FF
7. Optimize tcp server by using new `espconn_recv` ;
8. Fix an issue that getting error from string when print messages after upgrade;
9. Fix an issue that baudrate is not correctly set when it was set at 1,200;
10. Fix an issue that it should return error if the link id is wrong;
11. Fix an issue that DNS auto mode is used by default;
12. Fix a wrong link id issue when client connection number reaches maximum;

13. Fix an issue that error will be reported when the maximum connection number is more than 5;
14. Fix the message is incorrect when creating UDP if ip is a domain name;
15. Fix GSLP too long time error;
16. Fix that `AT+CIPSTART` causes busy if the server is connected at the same time;

ESP8266_NONOS_SDK_V2.2.0_18_02_06 Release Notes

System

1. Add APIs to ensure flash erasing safe;
 - `bool spi_flash_erase_protect_enable(void)` ;
 - `bool spi_flash_erase_protect_disable(void)` ;
2. Add `-DUSE_OPTIMIZE_PRINTF` in third_party/Makefile;
3. Update libc.a & libgcc.a;
 - libc.a from newlib 2.0.0, libgcc.a from gcc 4.8.5
 - Strip the functions which are already in rom code
 - Add a readme in lib folder to show how to strip the origin libraries
4. Update scripts to generate SSL related binaries;
5. Put libm.a into .irom0.text;
6. Compile some libraries with `-ffunction-sections -fdata-sections` ;
 - Modify ld to put this.text.* into .irom0.text
7. Remove `time()` function from libmain;
8. Fix issues of deep-sleep sleep 0 or sleep for a long time;
9. Fix an issue about driver compiling;
10. Fix `ets_delay_us` declaration;
11. Fix `os_malloc` declaration;

Examples

1. Add an example for WPA2 enterprise;
2. Update IoT_Demo project, fix user sector error;
3. Update mqtt demo project;

LWIP & espconn

1. [LWIP] Add LWIP source codes in the third_party folder;
2. [LWIP] Redefine err_t in lwip;
3. [LWIP] Fix the sequence number error of RST+ACK;
4. [LWIP] Fix an issue that two or more pbuf will be used when sending one TCP packet with `LWIP_NETIF_TX_SINGLE_PBUF` enabled;

5. [LWIP] Fix the length of TCP data in one packet is more than 1460;
6. [espconn] Fix an issue that duplicate UDP packet may be sent by espconn_sendto;
7. [espconn] Enable block option for fetching the proactive data;
8. [espconn] Manual fetch the receive data after the communication ends;

mbedTLS

1. Add mbedTLS source codes in the third_party folder;
2. Fix an issue that mbedTLS may memory leak in some cases when ESP8266 running as SSL/TLS client;
3. Fix an issue that the sent callback may not be called in some cases;
4. Fix load cert failure if the private key is in front of the cert in the esp_cert_private_key.bin;
5. Fix disconnect callback function never be called;
6. Speed up mbedtls handshake process;
7. Fix `already freed` and exception when esp8266 acts as SSL/TLS server;

Wi-Fi

1. Update libphy.a to version 1136;
2. Add APIs to set WPA2 Enterprise identity;
 - `int wifi_station_set_enterprise_identity(u8* identity, int len);`
 - `void wifi_station_clear_enterprise_identity(void);`
3. Add an example for WPA2 Enterprise;
4. Add support for passive scan;
5. Add support for scan threshold and dwell time;
6. Add APIs to set country code;
7. Add support for recording more information of scanned AP;
8. Fix the WPA/WPA2 PTK/GTK reinstallation vulnerability issue;
9. Fix softAP wrong behavior after calling `system_timer_reinit`;
10. Update esp_init_data_default.bin to v08;
 - Adjusted the default target power, from the 34th byte to the 39th byte of esp_init_data_default.bin, lower the target power of each level, optimized the frequency spectrum Mask and the EVM.
11. Add keep connection for station to keep connection with AP;
12. Add softAP distributes station ip event;

History Info.

ESP8266_AT_V1.5.1_17_11_06 Release Notes

1. Fixed the WPA2 KRACK issue.
2. Fixed the issue of wrong messages being displayed after upgrading the firmware.

ESP8266_NONOS_SDK_V2.1.0_17_05_05 Release Notes

System

1. Fix and update the license;
2. Add definitions of ROM functions;
3. Add efuse mac crc, save efuse mac into the system parameter area of flash, as a backup mac;
4. Implement `uart_div_modify`, which can support a 32-bit `DivLatchValue` in the SDK instead of the ROM one, and also remove `uartdivmodify` from the `ld` file;
5. Reduce iRAM usage by transferring some functions to flash;
 - add weak function `void user_spi_flash_dio_to_qio_pre_init(void)`. If the dio to qio flash mode is not used, users can add an empty `user_spi_flash_dio_to_qio_pre_init` on the application side to reduce iRAM usage;
6. Fix WDT in `system_restart`;
7. Fix Write & Read issue in SPI overlap mode;
8. Support 8MB & 16MB spi flash;
9. Update boot v1.7;
10. Support 8MB & 16MB spi flash;
11. Try boot the first bin for 3 times. If it fails, then boot the backup bin;
12. Fix http packet error, BBP301;
13. Support long periods of deep sleep;
14. Fix NMI handle crash on unaligned memory access, BBP309;

Lwip

1. Add set and get dns server APIs:
 - `espconn_dns_setserver`
 - `espconn_dns_getserver`
2. Fix 2038 overflow bug in `sntp_get_current_timestamp`;
3. Fix MTU negotiate bug;

AT

1. Add new commands, `AT+UART?` and `AT+UART_DEF?`;
2. Add new command, `AT+SYSRAM?`;
3. Add new commands, `AT+SYSIO` series;
4. Add new command, `AT+CWHOSTNAME`;
5. Add new command, `AT+SYSADC?`;
6. Add new commands, `AT+CIPSNTPCFG` and `AT+CIPSNTPTIME`;
7. Add new commands, `AT+CIPDNS_CUR` and `AT+CIPDNS_DEF`;
8. Support a maximum of 8 stations;
9. Modify keepalive count to 3 times;
10. Fix scan hidden ssid issue in `AT+CWLAP`;
11. Fix the issue of the UART stop bit being 0 when queried for the first time;
12. Fix MAC addr conflict in AP+STA mode;
13. Add new commands, `AT+RFAUTOTRACE`;

WiFi

1. Optimize the RF frequency calibration workflow, having the frequency trace disabled by default;
 - users can call `system_phy_freq_trace_enable` in `user_rf_pre_init` to enable it;
2. Update `libphy.a` to version 1134_0;
3. Allow sending a broadcast ESP-NOW packet, but make sure that the packet is unencrypted;
4. Fix soft queue error;
5. Fix `EVENT_STAMODE_AUTHMODE_CHANGE` event mode info;
6. Fix `Imac` assert;
7. Fix bug in sniffer mode;
8. Fix arp loss continuously issue;
9. Fix bug in WiFi event;
 - auth mode changed event cannot be throw when station is in the process of scanning;
 - error old auth mode and new auth mode;
 - op mode change process cannot be blocked, so add an event to notify the caller that op mode is changed;
10. Fix the bug in mic failure handler;
11. Fix the bug which causes failure of connection to an AP with shared WEP;
12. Fix the bug which causes failure of connection to an AP with hidden ssid;
13. Fix softAP deauth;
14. Fix reconnect policy when trying to connect to an AP that does not exist;
15. Fix scan issue;
16. Fix extra bytes in UDP broadcast packet, BBP310;

ESP8266_NONOS_SDK_V2.0.0_16_08_10 Release Notes

Optimization:

1. Changed the license of some source files to espressif MIT.
2. Updated `libphy.a` to 1055, fixed an issue of large current in Light-sleep.
3. Updated AT+ to 1.3.0:
 - Added Light-sleep wakeup command, `AT+WAKEUPGPIO`;
 - Fixed abnormal `AT+CWDHCPS` IP allocation;
 - Added `at_sdio` demo under example directory.
4. Fixed probable system default when calling `cur` and `def` interfaces.
5. Fixed the issue of high current in Deep-sleep mode without disabling SPI first.
6. Fixed an issue where the SDK would crash when switching from AP to Station mode by calling `wifi_set_phy_mode`.
7. Updated secondary boot loader to v1.6:
 - Supports AT + based on SDIO;
 - Supports entering testing mode through GPIO.
8. Added support for MXIC Flash QIO mode.
9. Fixed exception caused during TCP handshake and retransmission.
10. Fixed issues in ESP-NOW.

11. Added ESP-PAIR (Simple-Pair) feature, for APIs please refer to ESP8266 SDK API Guide.
12. wpa2-enterprise time function derivation and time check disable can be set by users.
13. Support for PEAP/TTLS in wpa2-enterprise, for APIs please refer to ESP8266 SDK API Guide.
14. Added mqtt demos under examples directory.
15. Other issue fixes.
16. Resolved an issue that RF_Init_data sector may be broken in stress test. Provided a function `user_rf_cal_sector_set` which has to be added in application by software developer. More details about `user_rf_cal_sector_set` refer to documentation "2C-ESP8266_SDK_API Guide". (Resolved in ESP8266_NONOS_SDK_V1.5.4.1)
17. Fix a potential risk that will cause rf not work after external reset. (Resolved in ESP8266_NONOS_SDK_V1.5.4.1)
18. Add SDIO AT support. (Resolved in ESP8266_NONOS_SDK_V1.5.4.1)
19. Fix a potential bug in espconn. (Resolved in ESP8266_NONOS_SDK_V1.5.4.1)

Notes:

`esp_init_data.bin` has to be downloaded into flash at least once. Download `blank.bin` to initialize the sector stored RF_CAL parameter (set by `user_rf_cal_sector_set`), and download `esp_init_data.bin` into flash, when the system needs to be initialized, or RF needs to be calibrated again.